## **HellermannTyton**



Article Number: 170-03013

Description: Expandable Braided Sleeving, Fray Resistant, .75" Dia.,

PET, Black, 75 ft/reel

Base Data		
	Local Order Number	170-03013
	Туре	BSPSC340
	Color	Black (BK)
	Features and Benefits	<ul> <li>Cuts with scissors without fraying ends enables field installations without need for hot knife.</li> <li>Material construction offers excellent abrasion and cut-through protection as well as inertness to common chemicals and fungus.</li> <li>Expands to 150% of easy installation and reduced assembly time requirements.</li> </ul>
	Quantity Per	reel
	Product Description	A versatile and economical general purpose braided sleeving that resists fraying when cut with ordinary scissors.
	Short Description	Expandable Braided Sleeving, Fray Resistant, .75" Dia., PET, Black, 75 ft/reel
Product Dimensions		
	Length L (Imperial)	75.0ft
	Length L (Metric)	22.9m
	Reel Length (imperial)	75.0ft
	Bundle Diameter Min. (Imperial)	0.625"
	Bundle Diameter Min. (Metric)	15.9mm
	Bundle Diameter Max. (Imperial)	1.0"
	Bundle Diameter Max. (Metric)	25.4mm
	Nominal Diameter (Imperial)	3/4"
	Nominal Diameter (Metric)	19.1mm
Material and Specifications		
	Material	Polyester (PET)
	Material Shortcut	PET
	Flammability	UL 94 V0

generated on: 4/4/2017

## 170-03013



Material and Specifications	Operating Temperature	-94°F to +248°F (-70°C to +125°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	75.0ft
	Package Quantity (Metric)	75.0ft
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	0.8325lbs
	Weight (Metric)	0.38kg

generated on: 4/4/2017