

556-00239

HellermannTyton



Article Number: 556-00239

Description: Thermal Transfer Printer, Black, 1/pkg

Base Data	Local Order Number	556-00239
	Type	TT230SM KIT
	Color	Black (BK)
	Features and Benefits	<p>HellermannTyton's range of thermal transfer printers are designed to cover the needs of most users in an industrial environment.</p> <p>Premium TT4000+ printer series This series is intended for heavy-duty industrial applications. Various options such as the existing HellermannTyton perforator or cutter demonstrate the flexibility and power of this new printer.</p> <p>One high quality 300dpi print head is available and is ideally suited for high definition graphics such as 2d barcodes as well as standard bar coding, numbers and text. The TT4000+ printer is a highly effective and reliable printer able to produce medium and high volume labels, heatshrink, and Tiptags. Print speeds up to 125mm per second (5" per second) are possible dependant on the material you wish to print.</p> <p>Standard TT430 printer An entry-level 300dpi printer that is specifically designed to run HellermannTyton's standard range of adhesive labels and ShrinkTrak. The TT430 is best suited for those with small to medium volume print runs. The standard range of HellermannTyton ribbons can also be used.</p>
	Quantity Per	box
	Product Description	HellermannTyton's TT230SM thermal transfer printer is designed for low to medium volume printing of thermal transfer labels and ShrinkTrak. The TT230SM delivers optimal performance not found in other small desktop printers. This lightweight printer offers high speed, precision, and flexible printing with the ability to print on most HellermannTyton labels and ShrinkTrak. Used in conjunction with TagPrint Pro 3.0, the TT230SM will offer error-free printing and seamless operation.
	Technical Description	Thermal Transfer Printer, Black
	Short Description	Thermal Transfer Printer, Black, 1/pkg
	Product Dimensions	
	Length L (Imperial)	10.0"
	Width W (Imperial)	7.95"
	Height H (Imperial)	6.81"
	Print Method	Thermal Transfer

556-00239



Material and Specifications		
	Material	Plastic (PL)
	Material Shortcut	PL
	Operating Temperature	+40°F to +104°F (+4°C to +40°C)
	ROHS Compliant	Yes
	UL Listed (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1
	Package Quantity (Metric)	1
	Customs Number(Schedule B)	8443321050
	Weight (imperial)	4.41
	Weight (Metric)	2kg