

Article Number: 596-00207



Description: Solar Marker, Reflective, Non-Adhesive, WARNING: PV POWER SOURCE, 4" x 2", Vinyl, Red, 25/pkg

Base Data	
Local Order Number	596-00207
Type	PVPSSNAP4
Color	Red (RD)
Features and Benefits	<ul style="list-style-type: none"> <li>• Pre-Printed Solar Labels are made using high performance UV stable materials and adhesives for long outdoor life.</li> <li>• Designed to meet NEC and IFC standards for PV installation labeling, the pre-printed Solar labels come printed with the most common legends required by the AHJ (Authority Having Jurisdiction) used on large utility and scaled projects to ensure code compliance during inspection.</li> <li>• Labels are UV stable and made with special high bond adhesives to stick to both powder coat painted surfaces and baked enamel surfaces found on most disconnect switches and breaker boxes.</li> <li>• The printed inks meet the fire safety standards of the IFC (International Fire Code) and also meet the requirements of UL969 for high reflectivity and durability.</li> </ul>
Quantity Per	pack
Product Description	These HellermannTyton photovoltaic caution and power source markers are designed to meet the requirements of the National Electrical Code (NEC) International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Coiled markers are pre-printed, non-adhesive and made of a UV stable vinyl. Markers can be opened and snapped over cables for long-term, reflective, permanent identification. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed. Vinyl markers fit all standard PV cables or electrical metallic tubing (EMT) conduits.
Technical Description	Pre-Printed Solar Marker, Reflective, Non-Adhesive, Coiled, "WARNING: PHOTOVOLTAIC POWER SOURCE", 4" X 2", Red
Short Description	Solar Marker, Reflective, Non-Adhesive, WARNING: PV POWER SOURCE, 4" x 2", Vinyl, Red, 25/pkg
Product Dimensions	
Length L (Imperial)	2.0"
Length L (Metric)	50.8mm
Width W (Imperial)	4.0"
Width W (Metric)	101.6mm
Height H (Imperial)	2.0"
Height H (Metric)	50.8mm

596-00207



Material and Specifications		
	Material	Vinyl
	Material Shortcut	VL
	Halogenfree	Yes
	Operating Temperature	-18°F to +200°F (-29°C to +93°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
	Certification/Specification	NEC2011
Logistic and Packaging		
	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25
	Customs Number(Schedule B)	3919905060