596-00232



WARNING

ELECTRICAL SHOCK HAZARD

DO NOT TOUCH TERMINALS.

TERMINALS ON BOTH LINE AND
LOAD SIDES MAY BE ENERGIZED
IN THE OPEN POSITION

DC VOLTAGE IS ALWAYS PRESENT
WHEN SOLAR MODULES
ARE EXPOSED TO SUNLIGHT

Article Number: 596-00232

Description: Solar Label, WARNING ELECTRICAL SHOCK

HAZARD...DC VOLTAGE, 3.75" x 2.5", VL, Red, 50/roll

Base Data		
	Local Order Number	596-00232
	Туре	WESHLBLDC
	Color	Red (RD)
	Features and Benefits	 Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance. Supplied with an aggressive adhesive to ensure long life. Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections. Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.
	Quantity Per	reel
	Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Pre-Printed Solar Label, "WARNING - ELECTRICAL SHOCK HAZARD W/DC", 3.75" X 2.5", Red
	Short Description	Solar Label, WARNING ELECTRICAL SHOCK HAZARDDC VOLTAGE, 3.75" x 2.5", VL, Red, 50/roll
Product Dimensions		
	Width W (Imperial)	3.75"
	Width W (Metric)	95.25mm
	Height H (Imperial)	2.5"
	Height H (Metric)	63.5mm
Material and Specifications		
	Material	Type 443/552, UV Stable Flexible White Vinyl with Acrylic Laminate
	Material Shortcut	443/552
	Adhesive	Acrylic

generated on: 4/6/2017

596-00232



Material and Specifications	Halogenfree	Yes
	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	Certification/Specification	NEC2011
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919102055

generated on:

4/6/2017