

596-00233

HellermannTyton

Article Number: 596-00233

Description: Solar Label, WARNING ELECTRICAL SHOCK HAZARD, 3.75" x 2.0", VL, Red, 50/roll

Base Data	Local Order Number	596-00233
	Type	WESHLBL
	Color	Red (RD)
	Features and Benefits	<ul style="list-style-type: none"> • Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance. • Supplied with an aggressive adhesive to ensure long life. • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections. • Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.
	Quantity Per	reel
	Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Pre-Printed Solar Label, "WARNING - ELECTRICAL SHOCK HAZARD", 3.75" X 2", Red
	Short Description	Solar Label, WARNING ELECTRICAL SHOCK HAZARD, 3.75" x 2.0", VL, Red, 50/roll
Product Dimensions	Width W (Imperial)	3.75"
	Width W (Metric)	95.25mm
	Height H (Imperial)	2.0"
	Height H (Metric)	50.8mm
	Material and Specifications	
Material	Type 443/552, UV Stable Flexible White Vinyl with Acrylic Laminate	
Material Shortcut	443/552	
Adhesive	Acrylic	

596-00233



Material and Specifications	Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	Certification/Specification	IFC 2012
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919102055