

Article Number: 596-00235

WARNING:
TURN OFF PHOTOVOLTAIC
AC DISCONNECT PRIOR TO
WORKING INSIDE PANEL

Description: Solar Label, WARNING TURN OFF PHOTOVOLTAIC

PRIOR TO WORKING..., 4.125" x 2.0", VL, Red, 50/roll

Base Data		
	Lacel Order Norther	F00 0000F
	Local Order Number	596-00235
	Туре	WTOPVLBL
	Color	Red (RD)
	Features and Benefits	<ul> <li>Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance.</li> <li>Supplied with an aggressive adhesive to ensure long life.</li> <li>Meets NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.</li> <li>Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.</li> </ul>
	Quantity Per	reel
	Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Pre-Printed Solar Label, "WARNING - TURN OFF PV BEFORE WORKING", 4.12" X 2", Red
	Short Description	Solar Label, WARNING TURN OFF PHOTOVOLTAIC PRIOR TO WORKING, 4.125" x 2.0", VL, Red, 50/roll
Product Dimensions		
	Width W (Imperial)	4.125"
	Width W (Metric)	104.6mm
	Height H (Imperial)	2.0"
	Height H (Metric)	50.8mm
Material and Specifications		
	Material	Type 443/552, UV Stable Flexible White Vinyl with Acrylic Laminate
	Material Shortcut	443/552
	Adhesive	Acrylic

generated on: 4/6/2017

## 596-00235



Material and Specifications	Halogenfree	Yes
	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	Certification/Specification	UL969
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919102055

generated on: 4/6/2017