

151-28717

Article Number: 151-28717

Description: Adhesive Base, .75" x .75", .14" Max. Tie Width, .12" Hole Dia., PA66/Acrylate, White, 500/pkg



Base Data	
Local Order Number	MB3A10A2H4
Type	MB3A
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"> <li>• For use with 18 and 30 pound cable ties to provide stability when securing bundles.</li> <li>• Secures with acrylic based adhesive backing for heavy bonding applications</li> <li>• Can also be secured using two or four screws; providing multiple options.</li> <li>• 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.</li> </ul>
Quantity Per	bag
Product Description	HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.
Short Description	Adhesive Base, .75" x .75", .14" Max. Tie Width, .12" Hole Dia., PA66/Acrylate, White, 500/pkg
Product Dimensions	
Length L (Imperial)	0.75"
Length L (Metric)	19.0mm
Fixation Method	Screw Mounting and Adhesive
Width W (Imperial)	0.75"
Width W (Metric)	19.0mm
Cable Tie Width Max. (Imperial)	0.14"
Cable Tie Width Max. (Metric)	3.6mm
Height H (Imperial)	0.19"
Height H (Metric)	4.8mm
Mounting Hole Diameter D (Imperial)	0.12"
Mounting Hole Diameter D (Metric)	3.0 mm
Mounting Hole Centers (Imperial)	0.52"

151-28717



Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Adhesive	Acrylate with base of acrylic foam
	Adhesive Operating Temperature	to +194°F (+90°C)
	Flammability	UL 94 V2 (excluding adhesive)
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987