

120-05004



Article Number: 120-05004

Description: Cable Tie for AT2000, 18lb Tensile Strength, PA66, Natural, 5000/reel

Base Data	
Local Order Number	T18RA5000
Type	T18RA5000
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> • The AT2000 cable tie system is designed for automatic installation on bundles up to .75" and a minimum tensile strength of 18 lbs. • Available in reels of 5,000 each or bandoliers of 50 each.
Quantity Per	reel
Product Description	HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.
Technical Description	Cable Tie for AT2000, Natural
Short Description	Cable Tie for AT2000, 18lb Tensile Strength, PA66, Natural, 5000/reel
Product Dimensions	
Minimum Tensile Strength (Imperial)	18.0lbs
Minimum Tensile Strength (Metric)	80.0N
Length L (Imperial)	4.0"
Length L (Metric)	101.6mm
Power Supply unit	Electrical
Tie Closure	plastic pawl
Width W (Imperial)	0.1"
Width W (Metric)	2.5mm
Bundle Diameter Min. (Imperial)	0.03"
Bundle Diameter Min. (Metric)	0.7mm
Bundle Diameter Max. (Imperial)	0.75"
Bundle Diameter Max. (Metric)	20.0mm

120-05004



Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	US MILSPEC	MS3367-4-9
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	Certification/Specification	Cage Code 53421
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Metric)	5000